



Way of Life!

BORN OF GREATNESS.

INTRODUCING THE ALL-NEW

GIXXER SF 250



SOCS
SUZUKI OIL COOLING SYSTEM

ABS
DUAL CHANNEL

FI FUEL
INJECTION

#amGIXXER



Way of Life!

ABS DUAL CHANNEL

Dual Channel ABS - A lightweight and compact Dual-Channel ABS (Anti-lock Brake System) is included on both the front and rear wheels, ABS is the supplemental system which automatically controls the braking force efficiently and avoids wheel lock up due to the slippery road, the sudden change of road conditions or excessive braking in a certain controllable range.

FI FUEL INJECTION

The GIXXER SF 250 comes with advanced Fuel Injection Technology equipped with 6 sensors to calculate the optimum amount of fuel to be injected for better combustion efficiency, thereby improving fuel efficiency and providing accurate throttle response at all rpm to make your every ride even more exciting.

SOCS SUZUKI OIL COOLING SYSTEM

Suzuki Oil Cooling System (SOCS) - Oil cooling system in engines was first introduced by Suzuki to the world for creating lightweight and fast engines which provides high performance for a wide range of needs, from city-riding in traffic to serious sport riding using technologies derived from MotoGP such as weight-reduction and friction-reduction technologies. This unique technology also offers a refined acceleration that feels strong and linear. GIXXER SF 250 engine provides high output, compactness, low fuel consumption, high durability and ease of maintenance.



METALLIC TRITON BLUE



STRAIGHT AHEAD SPORTS BIKE



LED HEADLAMP



LED TAIL LAMP



DIGITAL INSTRUMENTATION



TWIN MUFFLER



REAR TYRE HUGGER



BRUSHED FINISH ALLOY WHEELS



SUZUKI EASY START SYSTEM



ALL-NEW 250cc ENGINE



6 SPEED GEAR BOX



CLIP-ON HANDLE BARS



STIFFER FRONT SUSPENSION



DUAL CHANNEL ABS WITH FRONT AND REAR DISC



WIDER TYRES



BIGGER FRONT DISC BRAKE



SPLIT SEAT AND GRAB RAIL

GENUINE ACCESSORIES




TANK PROTECTOR



TANK GRAPHIC



SADDLE BAGS



DC SOCKET



SEAT COVER



SMOKED VISOR

Engine

Engine Type:	4-Stroke, 1-Cylinder, Oil-Cooled
Valve System:	SOHC, 4 Valve
Displacement:	249 cm ³
Bore x Stroke:	76.0 mm x 54.9 mm
Engine Output:	26.5ps@9000rpm
Torque:	22.6Nm@7500rpm
Fuel System:	Fuel Injection
Starter System:	Electric
Transmission Type:	6 Speed, MT

Dimensions and Weight

Wheels:	Cast
Overall Length:	2010 mm
Overall Width:	740 mm
Overall Height:	1035 mm
Wheel Base:	1345 mm
Ground Clearance:	165 mm
Seat Height:	800 mm
Kerb Mass:	161 kg
Fuel Tank:	12 L

Suspension

Front:	Telescopic, Coil Spring, Oil Damped
Rear:	Swing Arm Type, Mono Suspension

Tyre Size

Front:	110/70R - 17 M/C - Radial Tubeless
Rear:	150/60R - 17 M/C - Radial Tubeless

Brake

Front:	Disc
Rear:	Disc

Electrical

Battery:	Maintenance-free, 12V 6Ah
Headlight:	LED
Tail light:	LED

Available at



dealership only



#Including 3 Years optional warranty.

Regd. Office, Sales & Marketing Office: 2nd Floor, Plot No. 1, Nelson Mandela Road, Vasant Kunj, New Delhi - 110 070. Fax: 011-4607 5418.

Ride safe. Wear a helmet. | Prices of the vehicles are available on our website. | Visit us at: www.suzukimotorcycle.co.in | [/Suzuki2whealers](https://www.facebook.com/Suzuki2whealers) | [#amGIXXER](https://www.instagram.com/amGIXXER) | [/Suzuki2whealers](https://www.youtube.com/channel/UCg1k1k1k1k1k1k1k1k1k1k1) | [/Suzuki2whealers](https://www.twitter.com/Suzuki2whealers) | [/Suzuki2whealers](https://www.instagram.com/Suzuki2whealers)

Specifications, appearances, equipments, colours, materials and other items of the Suzuki product shown in this leaflet are subject to change by manufacturers at any time without notice and they may vary depending upon local conditions and requirements. Please visit your local dealer for details of any changes. Actual body colour may differ from the colours in this leaflet. *ABS is not designed to shorten the braking distance. ABS cannot prevent wheel skidding caused by braking while cornering. Please ride carefully and do not overly rely on ABS.